



Comfort-Turner Barricade

'with an attractive price and quality'

application

industrial sites
schools
private property

series

Pro-Turner
Comfort-Turner
Eco-Turner

Just a solid, functional swing gate with an attractive price / performance ratio: that is our Comfort Turner swing gate. The gate has proven itself on a wide variety of locations. The Comfort-Turners turned out a sustainable solution for daily use everywhere.

All-round

The Comfort-Turner is available in versions Barricade, Rondissade and Carrade. You therefore always choose a gate with timeless, slick look. Access is always maximum: the gate is available in widths up to 3 meters (single version) and can swing open to 180 degrees.

Application

- industrial sites
- schools
- sports grounds
- private property

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 088 363 0666
info@bghekwk.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 015 202 400
info@bghekwk.be



Changes in construction and specifications reserved.
CTB-2004



www.bgfencing.com



Keep worries out

Swing gate Comfort-Turner Barricade

TECHNICAL SPECIFICATIONS

Comfort-Turner type single	100	120	150	200	250	300		
Clear opening*	1.050	1.200	1.500	2.100	2.550	3.000		
Comfort-Turner type double	200	240	300	400	500	600		
Clear opening*	2.070	2.370	2.970	4.170	5.070	5.970		
Posts								
Posts	80 x 80							
General								
Gate frame	60 x 40							
Bars	round 25							
Centre-to-centre	150	150	150	150	150	150		
Available heights	800	1.000	1.250	1.500	1.800	2.000	2.250	2.500

dimensions in ca. mm

* when opening gate wing(s) 180 degrees

Description

The Comfort-Turner is constructed of a steel gate wing and posts.

Gate wing

The Barricade gate wing is constructed of:

- Steel case profile 60 x 40 mm.
- Black plastic finish.
- Infill: bars round 25 mm placed between the upper and lower beam, centre-to-centre 150 mm.
- Gates of a 1.500 mm height or up are provided with a pointed comb (35 mm high sharp points).

Surface treatment and colours

- Hot-dip galvanized according to NEN-EN ISO1461 or hot-dip galvanized according to NEN-EN ISO1461 and then powder coated.
- Standard colours: RAL 6009 (pine green), RAL 7016 (antracite grey) and RAL 9005 (black). Other RAL-colours are available upon request.

Hinges and locks

- Drawbolt lock with Euro-profile cylinder and handle.
- Mounting with adjustable hinges.
- Single or double drop bolt: depending on width gate wing and version (single or double).

Assembly

- Gate posts: driving depth to 900 mm and poured with concrete.
- In case of a concrete floor: assembly with welded base plate.

Standards

- NEN EN 13241:2016.
- Wind category: Class 2 compliant with NEN EN 1991-1-4:2011



Options

- Door closer with widths up to 1.200 mm.
- Electric opener.

Variants

Other types of Comfort-Turner swing gates:

- Comfort-Turner Carrade: steel swing gate with welded mesh infill.
- Comfort-Turner Rondissade: steel swing gate with round bars placed through the upper and lower beam.

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 88 363 0666
info@bghekw.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 15 202 400
info@bghekw.be

Changes in construction and specifications reserved.
CTB-2004



www.bgfencing.com



Keep worries out

Samen zorgen voor minder CO₂