



Eco-Turner Promade

'functional and contemporary'

application

housing construction
sports grounds
private properties

series

Pro-Turner
Comfort-Turner
Eco-Turner

Looking for a solid, functional swing gate for daily use? Then choose our Eco-Turner. The gate derives its stability from two gate posts that have been secured in a concrete foundation. For the gate wing we combine a case frame with a contemporary welded mesh filling.

Comfortable and safe

The adjustable hinges and the functional handle lock guarantee a comfortable access to your property. The Eco-Turner can be locked with a Euro-profile narrow style lock. The interlocking parts and covered bolts effectively prevent forcing.

Application

Due to its robustness and attractive price / performance ratio we often place the Eco-Turner next to:

- sports grounds
- private properties
- housing construction projects

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 088 363 0666
info@bghekwerk.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 015 202 400
info@bghekwerk.be



Changes in construction and specifications reserved.
ETP-2004



www.bgfencing.com



Keep worries out

Swing gate Eco-Turner Promade

TECHNICAL SPECIFICATIONS

Eco-Turner type single	100	125			
Clear opening	1.000	1.250			
Comfort-Turner type double	200	250			
Clear opening	2.000	2.500			
Posts					
Posts	60 x 60	60 x 60			
General					
Gate frame	40 x 40	40 x 40			
Welded mesh panel	6/5/6	6/5/6			
Mesh size	50 x 200	50 x 200			
Available heights	1.000	1.250	1.500	1.800	2.000

dimensions in ca. mm

Description

The Eco-Turner is constructed of a steel gate wing and case posts 60 x 60 mm with a Promade infill. Opening of the wings is approx. 100 degrees.

Gate wing

The Promade gate wing is constructed of:

- Steel case profile 40 x 40 mm.
- Black plastic cover.
- Infill: welded mesh panel with horizontal double wires (round, 2 x 6 mm) and vertical single wire (round, 5 mm); mesh size 200 x 50 mm.

Surface treatment and colours

- Hot-dip galvanized according to NEN-EN ISO1461 or hot-dip galvanized according to NEN-EN ISO1461 and then powder coated.
- Standard colours: RAL 6009 (pine green), RAL 6005 (moss green) and RAL 9005 (black). Other RAL-colours are available upon request.

Hinges and locks

- Narrow style lock with day / night lock and aluminium handles.
- Mounting with adjustable hinges.
- Gate catcher with plastic cover.

Assembly

- Gate posts: driving depth to 900 mm and poured with concrete.
- In case of a concrete floor: assembly with welded base plate.
- Double version provided with drop bolt.

Standards

- NEN EN 13241:2016
- Wind category: Class 2 compliant with NEN EN 1991-1-4:2011
- 

Options

- Wall-attachment.
- Wall plate hinge.

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 088 363 0666
info@bghekwk.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 015 202 400
info@bghekwk.be

Changes in construction and specifications reserved.
ETP-2004



www.bgfencing.com



Keep worries out