



# Floriade park fencing

‘inconspicuous, but effective’

**applications**

parks  
gardens  
lawns, green areas

**series**

Blokkade  
Floriade

With Floriade park fencing you discourage unauthorized entry of green areas. You prevent motorists, scooters and cyclists destroying plants of unauthorized parking. A large, eye-catching fence is unnecessary. With the 30 or 40 cm high Floriade fence your green area is inconspicuously, but effectively protected.

**Application**

Floriade is ideal for public areas, like

- parks
- gardens
- lawns
- green areas (for example next to offices)

**Netherlands**

Habraken 2320  
NL-5507 TL Veldhoven  
P.O. Box 444  
NL-5500 AK Veldhoven

Tel.: +31 088 363 0666  
info@bghekwk.nl

**Belgium**

Wayenborgstraat 11  
B-2800 Mechelen

Tel.: +32 015 202 400  
info@bghekwk.be



Changes in construction and specifications reserved.  
FLO-2004



# Floriade park fencing

## TECHNICAL SPECIFICATIONS

Floriade type	30	40
Height	300	400
<b>Top rail</b>		
Tubular profile	41,5 x 1,75	41,5 x 1,75
<b>Posts</b>		
Tubular profile	60,3 x 1,75	60,3 x 1,75
Centre-to-centre	2.000	2.000
Driving depth	900	800

dimensions in ca. mm

### Construction

Floriade consists of:

- Top tubes / beams.
- Posts.
- Aluminium heads.

### Surface treatment and colours

- Hot-dip galvanized according to NEN-EN ISO1461 or galvanized and then powder coated.
- Standard colours: RAL 6009 (pine green), RAL 7016 (antracite grey) and RAL 9005 (black). Other RAL-colours are available upon request.

### Assembly

Posts

- Standard: driving depth to approx. 800 - 900 mm.
- In case of insufficiently compacted soil: assembly of a profiled anchor plate on the sunken part of the post.

Beams

- Run through aluminium heads; lock with special security screws.

### Variants

- Blokkade: drive-through protection in steel with posts combined with a beam guided through aluminium heads.

### Netherlands

Habraken 2320  
NL-5507 TL Veldhoven  
P.O. Box 444  
NL-5500 AK Veldhoven

Tel.: +31 088 363 0666  
info@bghekw.nl

### Belgium

Wayenborgstraat 11  
B-2800 Mechelen

Tel.: +32 015 202 400  
info@bghekw.be

Changes in construction and specifications reserved.  
FLO-2004



[www.bgfencing.com](http://www.bgfencing.com)



Keep worries out