



Pro-Turner Carrade

'the best swing gate in the market'

application

business parks
schools
sports grounds
industrial sites

series

Pro-Turner
Comfort-Turner
Eco-Turner

If you choose the Pro-Turner, you get the most solid and versatile swing gate that is for sale at the moment. This swing gate is available in several heights, widths and versions. You can choose from various drives. Because of the many possibilities the Pro-Turner perfectly matches the chosen fencing.

High security

The Pro-Turner is suitable for the high security segment. We assemble the heavy gate posts with hollow section to thick base plates, which are embedded in a reinforced foundation. The swing gates wing frame is constructed from a 60 x 60 mm case. We fill the frame with vertical bar fencing (Barricade, Rondissade or Stockade) or welded mesh Carrade. The locks are burglar proof.

Application

We apply the Pro-Turner at sites like:

- business parks
- industrial sites
- schools
- sports grounds

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 088 363 0666
info@bghekw.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 015 202 400
info@bghekw.be



www.bgfencing.com



Keep worries out

Swing gate Pro-Turner Carrade

TECHNICAL SPECIFICATIONS

Pro-Turner type single	100	125	150	200	250	300	350	400	500
Clear opening*	1.010	1.310	1.610	2.070	2.525	2.975	3.575	4.020	5.070
Pro-Turner type double	200	250	300	400	500	600	700	800	1000
Clear opening*	2.060	2.660	3.260	4.180	5.090	5.990	7.190	8.085	10.185
Posts									
Posts	80 x 80	80 x 80	80 x 80	100 x 100	110 x 110	110 x 110	110 x 110	140 x 140	140 x 140
Baseplate	-	-	option	option	option	option	option	250 x 250	300 x 300
Available heights	1.000**	1.250**	1.500	1.800	2.000	2.250	2.500		

dimensions in ca. mm

* when opening gate wing 180 degrees

** not available for gate from width 3.500 mm or up

Description

The Pro-Turner is constructed of a steel gate wing and posts with a Barricade infill. From width 3.500 m a diagonal tensioning cable is applied.

Gate wing

The Barricade gate wing is constructed of:

- Steel case profile 60 x 60 mm.
- Black plastic finish.
- Infill: welded mesh panel with horizontal double wires (round, 2 x 8 mm) and vertical single wire (round, 6 mm); mesh size 200 x 50 mm.
- Gates of a 1.500 mm height or up are provided with a pointed comb (35 mm high sharp points).

Surface treatment and colours

- Hot-dip galvanized according to NEN-EN ISO1461 or hot-dip galvanized according to NEN-EN ISO1461 and then powder coated.
- Standard colours: RAL 6009 (pine green), RAL 7016 (antracite grey) and RAL 9005 (black). Other RAL-colours are available upon request.


Hinges and locks

- Mounting with adjustable hinges.
- Draw bolt.
- Catch plate.

Assembly

- Gate posts: driving depth to 900 mm and poured with concrete.
- In case of a concrete floor: assembly with welded base plate.

Standards

- NEN EN 13241:2016
- Wind category: Class 2 compliant with NEN EN 1991-1-4:2011
- 

Options

- Wall-attachment.
- Wall plate hinge.
- Anti-climb protection: barbed wire, razor blade tape or rotating pointed segments.
- Escape lock with aluminium shield and blind case (with gates of 2.000 mm width or up).
- Door closer (with gates of max 1.250 mm width).
- Drives: GT-drive for gates up to 3.000 mm width. BT-drive from width 3.000 mm or up. The clear opening is slightly narrower due to the hinges in the clear opening of the gate. Type post changes to 120 x 120 mm.
- Shield.
- Clear opening approx. 6.000 mm (single version).
- Clear opening approx. 12.000 mm (double version).

Variants

Other types Pro-Turner swing gates:

- Pro-Turner Barricade: steel swing gate with round bars placed between the beams.
- Comfort-Turner Rondissade: steel swing gate with round bars placed through the upper and lower beam.
- Comfort-Turner Stockade: steel swing gate with square bars placed through the upper and lower beam.

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 088 363 0666
info@bghekw.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 015 202 400
info@bghekw.be

Changes in construction and specifications reserved.
PTC-2004



www.bgfencing.com



Keep worries out

Samen zorgen voor minder CO₂