



Rondissade bar fencing

'safety with a luxurious appearance'

applications

business parks
industrial sites
schools
sports grounds

series

Barricade
Rondissade
Stockade
Mikasade
Educade

Characteristic of Rondissade vertical bar fencing are the vertical, round bars that run through the horizontal beams. Many of our customers find this version aesthetically appealing. The hidden connection between posts and bar panels further strengthens this. Black plastic covers on the posts complete the picture.

Robust and maintenance-free

In order to firmly anchor the Rondissade vertical bar fencing for years, B&G drives the posts deep into the soil. The hidden connection between posts and bar panels promote safety and prevent unwanted disassembly. This fence also meets the highest quality standards so customers can rest assured on a maintenance-free fence for years to come.

Application

Rondissade vertical bar fencing is applicable on sites where a secure enclosure with a luxury appearance is desired. For example:

- business parks
- industrial sites
- schools
- sports grounds

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 88 363 0666
info@bghekwk.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 15 202 400
info@bghekwk.be



Rondissade bar fencing

TECHNICAL SPECIFICATIONS

Rondissade type	100	125	150	180	200	225	250
Height fence	1.000	1.250	1.500	1.800	2.000	2.250	2.500
Posts							
Dimension posts	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60
Driving depth	900	900	900	900	900	900	900
Bar panel							
Dimensions bars	round 25	round 25	round 25	round 25	round 25	round 25	round 25
Bar tops	straight	straight	bevelled	bevelled	bevelled	bevelled	bevelled
Beams	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25

dimensions in ca. mm

Construction

Panel

- Beams: steel case 50 x 25 mm.
- Bars: round 25 mm, centre-to-centre 150 mm. Bars are provided with bevelled tops with panels of 1.500 mm height or up.

Posts

- Square case 60 x 60 mm.
- Finish: black plastic cover.

Surface treatment

- Hot-dip galvanized according to NEN-EN ISO1461 or galvanized and then powder coated.
- Standard colours: RAL 6009 (pine green), RAL 9005 (black) and RAL 7016 (antracite grey). Other RAL-colours are available upon request.

Options

- Barbed wire (3 rows).
- Base plate: for assembly on concrete.

Assembly

Posts

- Standard: driving depth of approx. 900 mm.
- Centre-to-centre distance: 3.005 mm.
- In case of a concrete floor: assembly with welded base plates.

Bar panels

- Hidden connection with posts by means of plastic plugs and M8 end-to-end connections.

Solutions for height differences

- Slope panels (top beams run parallel to the slope).

Standards

- Wind category: Class 2 compliant with NEN EN 1991-1-4:2011

Variants

Other types of bar fencing are:

- Barricade: steel bar fencing with round bars placed between the upper and lower beams.
- Stockade: steel bar fencing with square bars placed through the upper and lower beams.
- Mikasade: distinctive steel bar fencing with round bars placed vertically and diagonally against the beams.
- Educade: child friendly steel bar fencing with round bars placed between the upper and lower beams.

Netherlands

Habraken 2320
NL-5507 TL Veldhoven
P.O. Box 444
NL-5500 AK Veldhoven

Tel.: +31 88 363 0666
info@bghekwk.nl

Belgium

Wayenborgstraat 11
B-2800 Mechelen

Tel.: +32 15 202 400
info@bghekwk.be

Changes in construction and specifications reserved.
RON-2008



www.bgfencing.com



Keep worries out