



Educade

'child friendly, in bright

applications
 industrial sites
 office parks
 transport companies

series
 Barricade
 Educade
 Palissade
 Rondissade

For fencing of schools, playgroups and day nurseries B&G developed Educade, the child friendly chain link fencing. With this fencing, that is available in many bright colours, you do not only keep the children on your grounds. It also serves as a clear boundary for unwanted visitors. .

Strict requirements

With Educade we meet the strictest requirements in the field of child friendliness. This fencing for example has no sharp or protruding parts. It is impossible to step on the fence. In this way we prevent unwanted climbing. By assembling the lower beam close to the ground level, we prevent children to crawl under the fence.

Application

- schools
- playgroups
- day nurseries
- playgrounds



Changes in construction and specifications reserved. Version ED-0218

Educade type	100	125
Height	1010	1260
Bar panel		
Bars (round mm)	22	22
Beams	50 x 25	50 x 25
Centre-to-centre	100	100
Posts		
Posts	60 x 60	60 x 60
Centre-to-centre	3005	3005
Driving depth	900	900

Dimensions in ca. mm.

Version

Bar panel

- beams: steel hollow section
- bars: round, between the beams

Posts

- square hollow section
- finish: black plastic cover

Surface treatment

- galvanized
- galvanized, then powder coated according to the Duplex-system

Standard colours

- RAL 6009 (pine green)
- RAL 6005 (moss green)
- RAL 9005 (black)

Other RAL-colours are available upon request

Options

- Educade swing gate, with comparable child friendly

Assembly

Posts

- standard: driving depth of approx. 900 mm.
- in case of insufficiently compacted soil: assembly of a profiled anchor plate on the sunken part of the post
- in case of a concrete floor: assembly with welded base plates
- centre-to-centre distance: 3005 mm.

Bar panels

- blind connection with posts by means of plastic plugs and M8 end-to-end connections

Cope with heights differences by:

- slope panels (top beams run parallel to the slope)
- assembly in a cascading way (top beams run horizontally))

B&G Fencing

Industrieweg 187a
5683 CC Best
Postbus 66
5680 AB Best

Tel.: (0499) 363 666
Fax: (0499) 399 945
info@bghekwk.nl

België

Wayenborgstraat 11
2800 Mechelen

Tel.: (015) 202 400
Fax: (015) 206 200
info@bghekwk.be